



REVERSE OSMOSIS WATER TREATMENT

250 GALLONS TO 10,000 GALLONS PER DAY
SYSTEM VOLUMES BASED ON SOFT WATER INLET TEMPERATURE OF 77 DEGREES

E.T.L. LISTED

STANDARD FEATURES

GLYCERIN GAUGES • PERMEATE AND CONCENTRATE FLOW METERS • STAINLESS STEEL MEMBRANE HOUSINGS • THIN FILM MEMBRANES • STAINLESS STEEL DELIVERY PUMP • U.L. LISTED ELECTRICAL COMPONENTS • RECYCLING VALVE • STAINLESS STEEL/ OR ALUMINUM FRAME AND SHROUD • 5 MICRON PREFILTER • WATER LEVEL CONTROL SWITCHES AND AUTO-FLUSH TIMER.

APPLICATIONS

SELF SERVICE AND AUTOMATIC CAR WASHES

3500 to 10,000 Gallons Per Day



43" Wide 60" High 24" Deep

SPECIFICATIONS:

ELECTRICAL: 110V / 230 V/ 1 or 3 PHASE
50 or 60 HZ
WATER: 30 PSI MINIMUM

250 to 3,000 Gallons Per Day



18" Wide 50" High 18" Deep

OPTIONS:

CAR WASH DELIVERY SYSTEMS • TDS METER •
STORAGE TANKS • SALT WATER SYSTEMS •
CARBON FILTERS

A-OK EQUIPMENT & SUPPLY CO., INC.

Designers • Manufacturers • Distributors of Quality Wash Systems at Affordable Prices
6031 Pillsbury Ave. So., Minneapolis, MN 55419 • (612) 866-2555
Nationwide: 1-800-328-3783 • Minnesota: 1-800-762-3795 • Fax: (612) 866-2562
Web: www.aokequipment.com • E-mail: carwash@aokequipment.com

